

# VIBRATORY PLOW



# SP11/SP15

## Your Service Drop Plowing Solution.

New compact plows from the worldwide leader. When you choose equipment, choose a manufacturer that understands your business. The Vermeer® SP11 and SP15 compact vibratory plows are designed specifically for irrigation, last-mile and service-drop installations. The SP11 and SP15 feature a common design, but are available with your choice of an 11 hp (8 kw) or 15 hp (11 kw) engine to meet your unique application needs.

Whether the project is a service drop, irrigation work, cable installation or an underground dog fence, SP11 and SP15 plows perform — contact your local dealer for more information today!





**A pivoting rear-blade design with removable chute** allows plowing in existing aboveground connections and offers easier and quicker cable-drop removal. The pivoting plow blade improves the unit's turning capabilities and maneuverability.



**Steel shielding** provides superior protection over plastic shielding; it offers more resistance to everyday abuse for increased machine durability and reliability.



**An operator-presence feature** is standard on the SP11 and SP15 for safety. The operator-presence feature automatically shuts off the engine when the operator releases the handle (when the ground-drive or plow shaker is engaged).



**Vermeer Manufacturing Company**  
1210 Vermeer Road East  
P.O. Box 200  
Pella, Iowa 50219 U.S.A.  
Phone: (641) 628-3141  
Fax: (641) 621-7734  
International fax: +1 (641) 621-7730  
www.vermeer.com

**For more information, call:**  
**1-888-VERMEER**  
1-888-837-6337 (U.S.A. only)

**Europe, Middle East and Africa Inquiries:**  
Vermeer International  
P.O. Box 323  
4460 AS Goes  
Netherlands  
Phone: +31 113 272700  
Fax: +31 113 272727

Vermeer Manufacturing Company reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. VERMEER and VERMEER LOGO are registered trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. KOHLER is a trademark of Kohler Company.

## SP11/SP15 Specifications

### General

Basic machine w/ 12" (30 cm) blade  
Height: 45" (114 cm)  
Weight: 1015 lb (460 kg)  
Length: 64.5" (163.8 cm)  
Width: 35.5" (90.2 cm)  
Ground clearance: 1.68" (4.3 cm)

### Engine

Model:  
SP11 — Kohler 11 hp (8 kw)  
SP15 — Kohler 15 hp (11 kw)  
Number of cylinders: 1  
Cooling medium: Air  
Displacement:  
SP11 — 24.3 in<sup>3</sup> (.4 L)  
SP15 — 26 in<sup>3</sup> (.4 L)  
Max. gross hp @ 3600 RPM:  
SP 11 — 11 hp (8 kw)  
SP15 — 15 hp (11 kw)  
Air cleaner: Dry dual element

### Fluid Capacities

Fuel tank capacity: 1.25 gal (4.7 L)  
Type of fuel: Gasoline  
Engine oil capacity: 4 pints (1.9 L)  
Hydraulic tank: 5.5 gal (20.8 L)

### Ground-Drive

Pump type: Hydraulic  
Pump flow @ 3600 RPM: 5.7 gpm (21.6 L/min)  
Filtration: 10 micron return, 100 mesh suction screen  
Tires:  
Option 1 — 18" x 8.5" (46 cm x 21.6 cm) — 8 turf  
Option 2 — 18" x 9.5" (46 cm x 24.1 cm) — 8 flotation lug  
Option 3 — 16" x 6.5" (41 cm x 16.5 cm) — 8  
Transport speeds:  
Forward — 0 mph — 1.8 mph (0 km/h — 2.9 km/h)  
Reverse — 0 mph — 1.2 mph (0 km/h — 1.9 km/h)

### Plow

Shaker type: Eccentric shaft  
Shaker drive: Mechanical (belt)  
Plow depth: 0" — 12" (0 cm — 30 cm)  
Plow width: .75" (1.9 cm)  
Blade types: Pull and feed, removable chute

### Options

Reel-carrier  
PortaBore attachment

**Worldwide coverage with a local touch.** Your independent, authorized Vermeer dealer knows your local conditions and is ready to provide expert sales, support, service and parts — wherever your job site.

